



**NOTES**

WALL PLATES CAN BE SIZED AND POSITIONED TO AVOID CUTTING INTO EXTERNAL SKIN OF INSULATION, DECIDING FACTORS TO BE WALL CORE THICKNESS AND PITCH OF ROOF. CARE SHOULD BE TAKEN THAT WALL PLATE IS NOT POSITIONED TOO NEAR THE INTERIOR FACE AS THIS MAY ENTAIL CUTTING INTO CONCRETE AT EXTERNAL SIDE.

WALL PLATE SHOULD BE 3m LONG AND JOINTS SHOULD BE LAPPED. THERE SHOULD BE 3 ANCHORS PER TIMBER. SHORTER TIMBER SHOULD ATTACH TO 3 RAFTERS MINIMUM.

RESTRAINT STRAPS (MIN. 30 x 5) CAN BE CAST INTO CONCRETE OR FASTENED THROUGH FOAM INTO CONCRETE - REFER TO DRAWING C-003 FOR DETAILS OF THIS.

**polarwall**

4, EXE UNITS  
COFTON ROAD  
MARSH BARTON  
EXETER  
EX2 8QW

TELEPHONE 01392 823300

WWW.POLARWALL.CO.UK

TITLE

ROOF PLATE DETAIL

THIS DRAWING AND THE INFORMATION CONTAINED IN IT IS © POLARWALL LIMITED 2018.

DRAWN  
FWJ SIMPSON

CHECKED  
A WHEELER

DATE  
24/07/2018

REVISION  
0

DRG. No.  
C-002